



**AO4716**

## N-Channel Enhancement Mode Field Effect Transistor **SRFET™**



### General Description



**SRFET™** AO4716 uses advanced trench technology with a monolithically integrated Schottky diode to provide excellent  $R_{DS(ON)}$  and low gate charge. This device is suitable for use as a low side FET in SMPS, load switching and general purpose applications. Standard Product AO4716 is Pb-free (meets ROHS & Sony 259 specifications).

### Features

$V_{DS} (V) = 30V$   
 $I_D = 16.5A (V_{GS} = 10V)$   
 $R_{DS(ON)} < 7m\Omega (V_{GS} = 10V)$   
 $R_{DS(ON)} < 10m\Omega (V_{GS} = 4.5V)$

**UIS TESTED!**

*Rg, Ciss, Coss, Crss Tested*



**SRFET™**  
Soft Recovery MOSFET:  
Integrated Schottky Diode

### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Maximum		Units
		10 Sec	Steady State	
Drain-Source Voltage	$V_{DS}$	30		V
Gate-Source Voltage	$V_{GS}$	±20		V
Continuous Drain Current <sup>AF</sup>	$I_{DSM}$	16.5	12.0	A
$T_A=70^\circ C$		13.0	9.6	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	180		A
Avalanche Current <sup>B</sup>	$I_{AR}$	25		A
Repetitive avalanche energy $L=0.3mH$ <sup>B</sup>	$E_{AR}$	94		mJ
Power Dissipation	$P_{DSM}$	3.1	1.7	W
$T_A=25^\circ C$		2.0	1.1	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150		°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>AF</sup>	$R_{\theta JA}$	31	40	°C/W
Maximum Junction-to-Ambient <sup>A</sup>		59	75	°C/W
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	16	24	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=1\text{mA}, V_{GS}=0\text{V}$	30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=30\text{V}, V_{GS}=0\text{V}$			0.1	mA
			$T_J=125^\circ\text{C}$		20	
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 20\text{V}$			0.1	$\mu\text{A}$
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1.3	1.6	2	V
$I_{D(\text{ON})}$	On state drain current	$V_{GS}=10\text{V}, V_{DS}=5\text{V}$	180			A
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=16.5\text{A}$		5.8	7.0	$\text{m}\Omega$
			$T_J=125^\circ\text{C}$		9.9	
		$V_{GS}=4.5\text{V}, I_D=13\text{A}$		8.2	10.0	$\text{m}\Omega$
$g_{FS}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=16.5\text{A}$		55		S
$V_{SD}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.33	0.5	V
$I_S$	Maximum Body-Diode + Schottky Continuous Current				5.5	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$		2154	2650	pF
$C_{oss}$	Output Capacitance			474		pF
$C_{rss}$	Reverse Transfer Capacitance			185		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		0.75	1.1	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, I_D=16.5\text{A}$		37	45	nC
$Q_g(4.5\text{V})$	Total Gate Charge			17.8	23	nC
$Q_{gs}$	Gate Source Charge			6.6		nC
$Q_{gd}$	Gate Drain Charge			7.6		nC
$t_{D(\text{on})}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, R_L=0.8\Omega, R_{\text{GEN}}=3\Omega$		6.8		ns
$t_r$	Turn-On Rise Time			7.2		ns
$t_{D(\text{off})}$	Turn-Off Delay Time			25.2		ns
$t_f$	Turn-Off Fall Time			5.8		ns
$t_{rr}$	Body Diode Reverse Recovery Time	$IF=16.5\text{A}, dI/dt=300\text{A}/\mu\text{s}$		12	18	ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$IF=16.5\text{A}, dI/dt=300\text{A}/\mu\text{s}$		10.5		nC

A: The value of  $R_{\theta JA}$  is measured with the device mounted on 1in 2 FR-4 board with 2oz. Copper, in a still air environment with  $T_k=25^\circ\text{C}$ . The value in any given application depends on the user's specific board design.

B: Repetitive rating, pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{C}$ .

C. The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to lead  $R_{\theta JL}$  and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using  $<300\mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with  $T_k=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

F. The current rating is based on the  $\leq 10\text{s}$  thermal resistance rating.

Rev1:May 2007

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note E)

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

