



Alle technischen Daten wurden unter Laborbedingungen ermittelt und können im Praxisbetrieb abweichen.
Es handelt sich bei den Angaben weder um Beschaffheits- noch um Haltbarkeitsgarantien.
All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding; particularly the information does not constitute or provide any legal guarantees ("Beschaffheitsgarantie" or "Haltbarkeitsgarantie").

Characteristics

General Characteristics	Standard	Value
number of contacts		10
termination technique		crimp
wire gauge		0,14 mm ² - 2,5 mm ² AWG 26 - AWG 14
max. insulation diameter		3,7 mm
flammability	UL 94	V-0
Electrical Characteristics	Standard	Value
rated voltage	IEC 60664-1	250 V (UL/CSA: 600 V)
pollution degree	IEC 60664-1	3
installation (overvoltage) category	IEC 60664-1	3
material group	IEC 60664-1	2
rated impulse withstand voltage	IEC 60664-1	6 kV
rated current $T_{amb} = 40^{\circ}\text{C}$		10 A
current carrying capacity	IEC 60512-5-2	see derating curve
contact resistance	IEC 60512-2-1	$\leq 5 \text{ m}\Omega$
insulation resistance	IEC 60512-3-1	$\geq 10^{10} \Omega$
Climatical Characteristics	Standard	Value
climatic category	IEC 60068-1	40 / 125 / 21
upper temperature	IEC 60512-11-9	+125 °C
lower temperature	IEC 60512-11-10	-40 °C
Mechanical Characteristics	Standard	Value
mechanical operation	IEC 60512-9-1	≥ 500 mating cycles
Materials	Standard	Value
insert		PA
contacts		CuZn (brass)
contact plating		Ag (silver) / Au (gold)
color		black

Gewicht (errechnet) / Calc WT : 8 g	Zul. Abw./Tolerances :	ISO 2768-m	DIN / ISO 13715	Maßstab / Scale : 1:1	A3
Prüfmaß / Testdimension	Gez. Drawn 12.11.2019 PWOELFFLE				
Teileindex / Partindexnumber:	Status Released	CUSTOMER DRAWING			
Bagatelle change:	Gepr. Checked 18.11.2019 MGRIMM				
01 201900008 12.11.2019 PWOLF	Amphenol Tuchel Industrial GmbH	M	C146 A10 001 E8	Blatt/Sheet 1	FAI2019-003740
Index Änderung/Description	Datum/Date	Name	Ers. f. / Replacement for : M-C146 A10 001 E8 Rev.neu		