


VINYL-FULLY INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS



MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

INSULATION MATERIAL : VINYL

TERMINAL MATERIAL : BRASS

DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL

A.W.G.	ITEM NO.	W mm(inch)	L mm(inch)	D mm(inch)	COLOR
22-16	FDFD1-110(5) ◎	3.2(.126)	19.0 (.748)	4.0 (.150)	RED
	FDFD1-110(8) ◎				
	FDFD1-187(5) *	5.0(.197)	20.5 (.807)		
	FDFD1-187(8) *				
	FDFD1-205(5)	5.7(.224)	20.2 (.795)		
	FDFD1-205(8)				
	FDFD1-250 *	6.6(.260)	22.2 (.874)		
16-14	FDFD2-110(5) ◎	3.2(.126)	19.0 (.748)	4.7 (.185)	BLUE
	FDFD2-110(8) ◎				
	FDFD2-187(5) *	5.0(.197)	20.2 (.795)		
	FDFD2-187(8) *				
	FDFD2-205(5)	5.7(.224)	20.2 (.795)		
	FDFD2-205(8)				
	FDFD2-250 *	6.6(.260)	22.2 (.874)		
12-10	FDFD5-250 *	6.6(.260)	24.2 (.953)	6.2 (.244)	YELLOW
	FDFD5-375 ◎	10.0(.394)	30.5 (1.201)		




ALL LISTED

◎ : NOT UL AND C-UL LISTED

* : ADDITIONAL SF CERTIFIED

VINYL-INSULATED DOUBLE CRIMP RECEPTACLE DISCONNECTORS



MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.

INSULATION MATERIAL : VINYL

TERMINAL MATERIAL : BRASS

DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL

A.W.G.	ITEM NO.	W mm(inch)	L mm(inch)	D mm(inch)	COLOR
22-16	FRD1-156	3.9 (.154)	23.3(.917)	4.0(.150)	RED
16-14	FRD2-156	3.9 (.154)	23.3(.917)	4.7(.185)	BLUE
	FRD2-195	4.9 (.193)			
12-10	FRD5-195	4.9 (.193)	25.1 (.988)	6.2(.244)	YELLOW



ALL LISTED