






SCREWDRIVER INSERTION
INSERIMENTO CACCIAVITE
WIRE INSERTION
INSERIMENTO CAVO



Single module for screwless terminal block - 45° angled - Modular version - Pitch 5mm - 1 pole

GENERAL INFORMATION

pitch:	5 mm
housing height:	14,30 mm
housing depth:	16.75 mm
dimensional class:	slow
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.45 × 2.45 mm
wire stripping:	max 9 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

spring releasing:	0.6 x 3.5mm
-	-

APPROVALS DATA



	-	-	UL 1059
current:	-	-	17A factory / 17A field
voltage:	-	-	300V
wire section:	-	-	12÷30AWG
torque:	-	-	-
FILE:	-	-	E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

(STD) **GN** **GY** **BK** **BL** **RD** **YL** **OG**

screw: n/a
clamp/spring: other colours: upon request
terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
01	MG101-5-DI	N/A	N/A	N/A